

BIPLASMA 3D

SCHEDA TECNICA

Revisione : 25/02/2022

Prodotto: **Biplasma 3d**

Categoria: Plasma 3D

Azienda: Loggia

General Characteristics

Application

Media Preparation



Testo da inserire



Application Methods



Testo da inserire

Application temperature:		°C
Relative humidity of application:		
Recommended thickness:		µm per coat
Dust dry:		h
Repaintable after:		h
Deep dry:		h
Tool cleaning:		

Painting:



Testo da inserire

Specific weight:		Kg/l
Viscosity:		cPs
pH:		
Solid in weight:		
Theoretical yield:		mq/l
Recommended coats of paint:		
Color:		
Appearance:		

Storage:



The unopened product, stored intact in a dry and cool place, has a storage life of not less than 24 months

After use carefully close the package and store it upside down.



Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

Safety Precautions:

For all information relating to the handling of the product as well as its correct disposal, please refer to the Safety Data Sheet.

Warnings

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

BVQI certified company for the UNI EN ISO 9001-2000 quality system.