

RAIN PROTEX

SCHEDA TECNICA

Revisione : 25/02/2022

Prodotto: **Rain Protex**

Categoria: Isolanti Fissativi

Azienda: Loggia

General Characteristics

Colorless siloxane water repellent for exteriors with excellent resistance to alkanes. It can be used as a colorless non-film-forming finish for concrete, mineral plasters, fiber cement panels, silico-limestone or brick masonry, mineral-based natural and artificial stone and wall paints.

Use

Suitable for the decoration of interior elements of classic or modern high-prestige buildings.

Media Preparation



The product must be used as it is on very crumbling surfaces or where a high quality penetration is desired. Eliminate from the surface any cracks which have a width greater than 0.3 mm.



Thoroughly clean the surface with suitable detergents or use water or steam. The latter methods are the most recommended thus the surface does not soak very much. Wait until the surface is completely dry. Apply the product up to a clear refusal of the surface. Cover the surface for 4-5 hours after the application of the product.



Application Methods



Brush or spray: ready to use. For spray application, use low pressure.

If the product is applied indoors, a continuous air exchange is required so that the water vapors escape. Apply the product on a carefully treated surface. Yield may vary according on the characteristics of the substrate. Do not apply the product under direct sunlight.

Application temperature:	+10÷ +35	°C
Relative humidity of application:	< 85%	
Recommended thickness:	80-120	µm per coat
Dust dry:	2-4	h
Repaintable after:	2-4	h
Deep dry:	24	h
Tool cleaning:	with water	

Specific weight:	0,95 ÷ 1,05	Kg/l
Viscosity:	2000-300	cPs
pH:	7-8	
Solid in weight:	3%	
Theoretical yield:	0,1 a 3 l/mq per mano a seconda delle capacità di assorbimento del supporto.	mq/l
Color	without color	
Appearance	milky	
Packaging:	1 - 5 - 10	l

Storage:



The unopened product, stored intact in a dry and cool place, has a storage life of not less than 24 months

After use carefully close the package and store it upside down.



Minimum storage temperature: + 5 ° C

Maximum storage temperature: + 30 ° C

Safety Precautions:

For all information relating to the handling of the product as well as its correct disposal, please refer to the Safety Data Sheet.

Warnings

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

Loggia Industria Vernici S.r.l. Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) – ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. www.loggia.it, E-mail commerciale@loggia.it.

BVQI certified company for the UNI EN ISO 9001-2000 quality system.